

## SmartLine

### SLN 700 SmartLine Non-Contact Radar Level Specification

34-SL-03-06, October 2020



#### Introduction

Part of the SmartLine® family of products, the SLN 700 is a high performance 80 GHz non-contact radar level transmitter offering high accuracy, stability over a wide range of level applications. SmartLine SLN 700 level transmitters are an ideal solution for demanding process level needs, with easy-to-use and low-maintenance character.

The SmartLine family is also fully tested and compliant with Experia® PKS, providing the highest level of compatibility assurance and integration capabilities. SmartLine easily meets the most demanding needs for level measurement applications.



Figure 1 —SLN700 Non-Contact Radar Level transmitter

#### Best in Class Features:

- 80 GHz FMCW technology
- Narrow beam, small blind zone & accurate measurement
- Immunity to temperature, pressure, most obstacles and dust
- False echo suppression option
- Easy setup, no dielectric constant dependence
- Small antenna size fits most process: easy to install
- High resolution: better accuracy and process detail
- Measuring range: up to 30 m (liquids) / 120 m (solids)
- Accuracy  $\pm 2$  mm
- Process Temperature range: -40 to 200 °C
- Process Pressure range: -1 to 25 bar
- Operating voltage: 12 to 30 V DC
- Output signal: 4 - 20 mA & HART®

#### Description

The SmartLine 80 GHz Non-Contact Radar Level transmitter utilizes Frequency Modulated Continuous Wave (FMCW) technology which has greater sensitivity and accuracy for level measuring applications.

### **Unique Out-of-the-Box, Full User Experience<sup>1</sup>**

The specification of the correct level transmitter for the level measurement is one of the root causes for many common field failure modes. This user experience is enhanced with the unique SmartLine Application and Validation Tool (AVT) found at <https://config.honeywellsmartline.com/>. This allows users to specify their tank level application and the options desired for their level transmitter. The AVT intelligently guides the user through the engineering process and electronically captures and documents the choices and inputs.

In addition to serving as engineering documentation, the AVT output also serves as input to the Honeywell order management system, thus ensuring correct input of the transmitter model. The additional advantage is a transmitter with configuration parameters already specified to match the targeted tank application. Errors are eliminated and the engineering effort is preserved from start to finish.

The SmartLine Application and Validation Tool also allows users to collaboratively use and share the active session with any web connected colleague or expert. This interactive, collaborative capability eliminates roadblocks and delays. Users can access resources to help start and finish the engineering task in a single effort. This online tool also dynamically reformats the user interface to display correctly on an IOS or Android™ device.

<sup>1</sup> will be available soon.

### **Diagnostics**

SmartLine transmitters all offer digitally accessible diagnostics which aid in providing advanced warning of possible failure events, minimizing unplanned shutdowns, providing **lower overall operational costs**

### **System Integration**

- SmartLine communications protocols all meet the most current published standards for HART®
- Integration with Honeywell's Experion® PKS offers the following unique advantages.
  - FDM Plant Area Views with Health summaries
  - The SLN series is Experion tested to provide the highest level of compatibility assurance.
- Display modular can be added or removed in the field
- 128 by 64 dot matrix graphics display
- Large PV font format supported. Echo stem plots with Distance to Product and Distance to Interface Configurable screen
- The Display supports English and Chinese languages.

### **Unique Indication/Display Options**

The SmartLine SLN series level transmitter's modular design accommodates a unique advanced graphics LCD display.



**Figure 2: Advanced Graphics LCD Display Features**

### **Modular Design**

To help contain maintenance and inventory costs, all SLN series transmitters are modular in design supporting the user's ability to change electronic modules without affecting overall performance. Electronic modules may be swapped with another electronics module without losing in-tolerance performance characteristics. With no performance effects, Honeywell's unique modularity results in **lower inventory needs and lower overall operating costs.**

### **Configuration Tools**

Integral Four Button Configuration Option is suitable for all electrical and environmental requirements, SmartLine offers the ability to configure the transmitter and display via four buttons.

### **HandHeld Configuration**

SmartLine transmitters feature two-way communication and configuration capability between the operator and the transmitter. This is accomplished via Honeywell's field-rated Multiple Communication Configurator.

### **FDM and FDM Express**

Honeywell's Field Device Manager (FDM) Software and FDM Express are available for managing HART® device configurations.

## Product Family

### **SLN700L-82 (80 GHz)**

for liquids in corrosive process applications



The SLN700L-82 is an 80 GHz FMCW radar transmitter for continuous level measurement of liquids under different process conditions. The excellent beam focusing can provide accurate and reliable measurement in regular or strongly corrosive liquids.

The SLN700L-82 can measure in process conditions with temperatures up to +200°C and pressures up to 25 bar. The antenna options permit to measure distances up to 30 m. It offers an extensive choice of flanged process connections from DN50 to DN150.

### **SLN700L-83 (80 GHz)**

for liquids in process applications for small vessels



The SLN700L-83 is an 80 GHz FMCW radar transmitter for continuous level measurement of liquids under different process conditions, especially in small vessels. The excellent beam focusing can provide accurate and reliable measurement from basic process to mild corrosive liquids, especially for small vessels.

The SLN700L-83 can measure in process conditions with temperatures up to +200°C and pressures up to 25 bar. The antenna options permit to measure distances up to 30 m. It offers an extensive choice of threaded process connections from ¾" to 3".

### **SLN700S-87 (80 GHz)**




for solids in process applications



The SLN700S-87 is an 80 GHz FMCW radar transmitter for continuous level measurement of solids under different process conditions. The excellent beam focusing can provide accurate and reliable measurement for most powder or bulk solids applications in storage vessels. Options for air purge or dust shield options optimize sensor performance in dusty conditions.

The SLN700S-87 can measure in process conditions with temperatures up to +200°C and pressures up to 25 bar. The antenna options permit to measure distances up to 120 m. It offers an extensive choice of flanged process connections from DN100 to DN150.

## General Specifications


	SLN700L-82	SLN700L-83	SLN700S-87
			
<b>Applications:</b>	Liquids Suitable for the strong corrosive liquids, vapours / foams	Liquids Suitable for mildly corrosive liquids; small vessels	Solids Storage vessel/process vessel or high dust environment
<b>Measurement range:</b>	0~30 m	0~10 m (SLN700L-83A) 0~30 m (SLN700L-83B/C/D/E)	0~120 m
<b>Measurement accuracy:</b>	±2 mm		±5mm
<b>Process temperature</b>	(-40~150) °C (-40~200) °C	(-40~130) °C (-40~200) °C	(-40~130) °C (-40~200) °C
<b>Process pressure</b>	(-0.1~2.5) MPa		(-0.1~0.3) MPa
<b>Antenna form:</b> (See <a href="#">Antenna</a> )	SLN700L-82A/B/C/D	SLN700L-83A/B/C/D/E	SLN700S-87A/B/C/D
<b>Antenna + Lens material:</b> (See <a href="#">Antenna</a> )	316L+FEP 316L+PTFE	316L+PTFE	316L+PP 316L+PEEK
<b>Process Connection</b> (See <a href="#">Antenna</a> )	Flange	Thread	Flange
<b>Seal Material</b>	FKM	FFKM	FKM
<b>Frequency:</b>	77-81 GHz		
<b>Signal output:</b>	4-20 mA & HART®		
<b>Power supply:</b>	2-wire (12~30) V DC		
<b>Housing Material:</b>	Polyester-coated aluminium		
<b>Weight</b>	SLN700L-82: approx. 5.1 to 18.4 kg SLN700L-83: approx. 1.8 to 3.5 kg SLN700S-87: approx. 4.8 to 8.6 kg		
<b>Ingress Protection level</b>	IP67		
<b>Unmeasurable area</b>	End of antenna		
<b>Measurement interval</b>	approx. 1 s		
<b>Adjust time</b>	approx. 3 s		
<b>Display resolution</b>	1 mm		
<b>Display</b>	128 × 64 pixels, with 4-button keypad		

## Operating Conditions – All Models

Parameter	Description	
<b>Environmental Operating temperature<sup>1</sup></b>	Device Operating range: -25 to 80°C Display operating range: -20 to 80°C	
<b>Temperature for storage and transport</b>	-40 to +80 °C	
<b>Relative humidity</b>	<95%	
<b>Power Supply 2-wire</b>	Standard type	(12~30) V DC
	Intrinsically safe	(12~30) V DC
	Power consumption	max.22.5 mA
	Ripples are allowed – <100Hz – (100~100K)Hz	U <sub>ss</sub> <1 V
		U <sub>ss</sub> <10 mV
<b>Cable parameters</b>	Cable entry/plug	M20x1.5/ ½'NPT cable entry, and M20x1.5/ ½'NPT blind plug
	Spring collecting terminals	Used for conductor with cross section of 2.5 mm <sup>2</sup>
<b>Output parameter</b>	Output signal	(4-20) mA/HART®
	Resolution	0.3 µA
	-2-wire load resistance	Refer to <a href="#">Figure 3</a>

<sup>1</sup> The ambient temperature limit for intrinsic safety differs. See section on Hazardous Locaiton Approvals.

### 2-wire load resistance



**Figure 3: 2-wire load resistance**


## Performance Under Rated Conditions – All Models

Parameter	Description
<b>Analog Output</b>	Two-wire, 4 to 20 mA
<b>Digital Communications:</b>	HART <sup>®</sup> 7 protocol
<b>Output Failure Modes</b>	<b>Compliance:</b> Honeywell Standard: <b>Normal Limits:</b> 3.8 – 20.8 mA <b>Failure Mode:</b> ≤ 3.6 mA and ≥ 21.0 mA
<b>Measurement accuracy</b>	Refer to figure on page 7
<b>Temperature drift</b>	±2 mm/10 K
<b>Repeatability</b>	±1 mm
<b>Dielectric constant (minimum)</b>	1.4
<b>Electromagnetic Compatibility and Radio Equipment</b>	EN 301 489-1 V2.2.0, EN 301 489-3 V2.1.1, EN 302 729 V2.1.1, EN 302 372 V2.1.1, EN 62311:2008
<b>Electrical Safety</b>	EN 61010-1:2010
<b>Vibration-proof</b>	Mechanical shock 10 m/s <sup>2</sup> , 10-150 Hz


## Measurement accuracy under reference conditions

Measuring distance from lower edge of flange or thread


SLN700L-82A/B/C/D	
Lens antenna	Beam Angle
DN50 (SLN700L-82A/B)	6°
DN80 (SLN700L-82C/D)	3°




SLN700L-83A	
Lens antenna	Beam Angle
¾" (SLN700L-83A)	14°




SLN700L-83B/C/D/E	
Lens antenna	Beam Angle
1½" (SLN700L-83B/C)	6°
3" (SLN700L-83D/E)	3°




SLN700S-87A/B/C/D	
Lens antenna	Beam Angle
DN80 (SLN700L-87A/B/C/D)	4°




## Antenna



<b>No.</b>	<b>SLN700L-82A</b>	<b>SLN700L-82B</b>	<b>SLN700L-82C</b>	<b>SLN700L-82D</b>
<b>Material</b>	316L+FEP 316L+PTFE	316L+FEP 316L+PTFE	316L+FEP 316L+PTFE	316L+FEP 316L+PTFE
<b>Process Connection</b>	DN50 DN80 DN100	DN50 DN80 DN100 DN150	DN80 DN100 DN125 DN150	DN80 DN100 DN125
<b>Features</b>	Anti-corrosion High Pressure Single radiator 150 °C	Anti-corrosion High Pressure Multi-fin radiator 200 °C	Anti-corrosion High Pressure Single radiator 150°C	Anti-corrosion High Pressure Multi-fin radiator 200 °C



<b>No.</b>	<b>SLN700L-83A</b>	<b>SLN700L-83B</b>	<b>SLN700L-83C</b>	<b>SLN700L-83D</b>	<b>SLN700L-83E</b>
<b>Material</b>	316L+PTFE	316L+PTFE	316L+PTFE	316L+PTFE	316L+PTFE
<b>Process Connection</b>	Thread G $\frac{3}{4}$ A Thread $\frac{1}{4}$ NPT	Thread G1 $\frac{1}{2}$ A Thread 1 $\frac{1}{2}$ NPT	Thread G1 $\frac{1}{2}$ A Thread 1 $\frac{1}{2}$ NPT	Thread G3 A	Thread G3 A
<b>Features</b>	Anti-corrosion	Anti-corrosion	Anti-corrosion	Anti-corrosion	Anti-corrosion



<b>No.</b>	<b>SLN700S-87A</b>	<b>SLN700S-87B</b>	<b>SLN700S-87C</b>	<b>SLN700S-87D</b>
<b>Material</b>	316L+PP/ 316L+PEEK	316L+PEEK	316L+PP/ 316L+PEEK	316L+PEEK
<b>Process Connection</b>	DN100 DN125 DN150	DN100 DN125 DN150	DN100 DN125 DN150	DN100 DN125 DN150
<b>Features</b>	Thread/purging Micro Pressure 130 °C	Thread/purging Micro Pressure with Radiator 200 °C	Universal/purging Atmospheric 130 °C	Universal/purging Atmospheric with Radiator 200 °C

## Housing Dimensions

### AG type housing

Material: Polyester Powder Coated Aluminum




Figure 4: AG type housing

## Dimensional Drawings




Figure 5: SLN700L-82A/C






Figure 6: SLN700L-82B/D




Figure 7: SLN700L-83A/B/C




Figure 8: SLN700L-83D/E




Figure 9: SLN700S-87A/B

## Hazardous Location Approvals

See manual for Special Conditions of safe use

AGENCY	TYPE OF PROTECTION
<b>IECEX</b> <b>TUR 20.0056X</b>	<b>Intrinsically Safe:</b> Ex ia IIC T6...T2 Ga Ex ia IIIC T85°C...T300°C Da
<b>ATEX</b> <b>TÜV 20 ATEX 8576 X</b>	<b>Intrinsically Safe:</b> II 1 G Ex ia IIC T6...T2 Ga II 1 D Ex ia IIIC T85°C...T300°C Da

Ambient Temperature (°C)	Process Temperature at the Antenna (°C)	Temperature Class of entire transmitter
-40 to +50	-40 to +50	T6/85 C
-40 to +60	-40 to +95	T5/100 C
-40 to +70	-40 to +130	T4/135 C
	-40 to +195	T3/200 C
	-40 to +200	T2/300 C

Intrinsic Safety Entity Parameter	4-20mA Version Terminals 1 & 2	RS485 Version Terminals 1 & 2	RS485 Version Terminals 4 & 5
Ui	30.6V	26.4V	6.5V
Ii	131mA	166mA	68mA
Pi	1.0W	1.1W	111mW
Ci	0	0	0
Li	102uH	0	102uH

# Model Selection Guide

Model Selection Guides are subject to change and are inserted into the specifications as guidance only.

## Model SLN700 Series Liquid/Solid Measurement Smartline Non Contact Radar Level Transmitter

Model Selection Guide  
34-SL-16-20 Issue 1

**Instructions**

- Select the desired Key Number. The arrow to the right marks the selection available.
- Make one selection from each Table (I, II and IX) using the column below the proper arrow.
- A(•) denotes unrestricted availability. Aletter denotes restricted availability.
- Restrictions follow Table IX.

Key Number    Table 1    Table 2    Table 3    Table 4    Table 5    Table 6    Table 7    Table 8    Table 9

SLN700 \_ - [ ] - [ ] - [ ] - [ ] - [ ] - [ ] - [ ] - [ ] - [ ]

KEY NUMBER	Application	Selection	Availability
	Liquid Level Measurement	SLN700L	↓
	Solid Level Measurement	SLN700S	↓

TABLE I		Antenna and Material Selections					Selection	L	S
a. Antenna type and materials	Antenna Type	Process temperature	Process Pressure	Lens Diameter	Options	Range			
	Flange with encapsulated antenna	-40 to +150 °C (-40 to +302 °F)	-1...25 barg (-14.5...362 psig)	50mm		30m	82A_	•	
		-40 to +200 deg C (-40 to +392 F)	-1...25 barg (-14.5...362 psig)	50mm		30m	82B_	•	
		-40 to +150 °C (-40 to +302 °F)	-1...25 barg (-14.5...362 psig)	80mm		30m	82C_	•	
		-40 to +200 deg C (-40 to +392 F)	-1...25 barg (-14.5...362 psig)	80mm		30m	82D_	•	
		-40 to +130 deg C (-40 to +266 F)	0...1 barg (0...14.5 psig)	80mm	Gimbal Flange	120m	87A_	•	
		-40 to +200 deg C (-40 to +392 F)	0...1 barg (0...14.5 psig)	80mm	Gimbal Flange	120m	87B_	•	
	Thread with integrated horn antenna	-40 to +130 deg C (-40 to +266 F)	-1...3 barg (-14.5...43.5 psig)	80mm		120m	87C_	•	
		-40 to +200 deg C (-40 to +392 F)	-1...3 barg (-14.5...43.5 psig)	80mm		120m	87D_	•	
		-40 to +130 deg C (-40 to +266 F)	-1...25 barg (-14.5...362 psig)	3/4"		10m	83A_	•	
-40 to +130 deg C (-40 to +266 F)		-1...25 barg (-14.5...362 psig)	1 1/2"		30m	83B_	•		
b. Lens materials		PTFE (-40 to +200 deg C)				___0_	k		
		FEP (-40 to +200 deg C)				___A_	a		
c. Seal materials		PEEK (-40 to +200 deg C)				___B_	•		
		PP (-40 to +110 deg C)				___C_	•		
		FKM (-40 to +200 deg C)				___0	•		
		FFKM (-20 to +200 deg C)				___A	e		

TABLE II		Connection Types	Material	Size	Rating	Selection	L	S
Process Connection	Flanges ANSI	316L		2"	Class 150lb RF	AS2A	c	
					Class 300lb RF	AS2B	c	
				3"	Class 150lb RF	AS3A	a	•
					Class 300lb RF	AS3B	a	
				4"	Class 150lb RF	AS4A	d	
					Class 300lb RF	AS4B	d	
	Flanges DIN	316L		DN50	DN50 PN40	DS5B	c	
				DN80	DN80 PN40	DS8B	a	
				DN100	DN100 PN40	DS1B	d	
					DN100 PN16	DS1A	•	
				DN125	DN125 PN40	DS1M	f	
					DN125 PN16	DS1N	•	
				DN150	DN150 PN40	DS1Z	f	
					DN150 PN16	DS1Y	•	
	Threaded Fittings ISO228 and ANS	316L		3/4" NPT		NS7A	h	
1 - 1/2" NPT					NS5A	m		
G 3/4"					GS7A	h		
G 1-1/2"					GS5A	m		
G 3"					GS8A	n		

TABLE III		Agency Approvals (see data sheet for Approval Code Details)	Selection	L	S
Approvals	No Explosion Protection Approvals Required		0	j	•
	ATEX Intrinsically Safe		C	•	•
	IECEX Intrinsically Safe		D	•	•
	NEPSI Intrinsically Safe		G	•	•

TABLE IV		ELECTRONICS SELECTIONS			Selection	L	S
a. Electronic Housing Material & Connection Type	Housing Material		Connection	Lightning Protection	A __ B __	j	•
	Polyester Powder Coated Aluminum		1/2 NPT	None			
		Polyester Powder Coated Aluminum		M20	None	j	•
b. Output/ Protocol	Analog Output		Digital Protocol		_ H _	•	•
	4-20mA dc		HART Protocol				
c. Customer Interface Selections	Indicator	Zero, Span & Config Buttons		Languages	_ _ 0 _ _ G	•	•
	None	None		None			
	Advanced	Yes		EN, CH			

TABLE V		CONFIGURATION SELECTIONS			Selection	L	S
a. Diagnostics	Diagnostics			1 _ _ _	•	•	
	Standard Diagnostics						
b. Advanced Measurement	Interface Options			_ 0 _ _	•	•	
	None - Standard Level						
c. Output Limit, Failsafe & Write Protect Settings	Write Protect	Fail Mode	High & Low Output Limits <sup>3</sup>	_ _ 1 _ _ _ 2 _ _ _ 3 _ _ _ 4 _	•	•	
	Disabled	High> 21.0mAdc	Honeywell Std (3.8 - 20.8 mAdc)				
	Disabled	Low< 3.6mAdc	Honeywell Std (3.8 - 20.8 mAdc)				
	Enabled	High> 21.0mAdc	Honeywell Std (3.8 - 20.8 mAdc)				
d. General Configuration	Factory Standard			_ _ _ S	•	•	

TABLE VI		CALIBRATION & ACCURACY SELECTIONS			Selection	L	S
Accuracy and Calibration	Accuracy		Calibrated Range	Calibration Qty	A	•	•
	Std Accuracy (+/-2mm)		Factory Std	Single Range			

TABLE VII		ACCESSORY SELECTIONS			Selection	L	S
a. Customer Tag	No customer tag			0 _ _	•	•	
	One Wired Stainless Steel Tag (Up to 4 lines 26 char/line)			1 _ _			
	Two Wired Stainless Steel Tag (Up to 4 lines 26 char/line)			2 _ _			
b. Unassembled Conduit Plugs & Adapters	No Conduit Plugs or Adapters Required			_ A 0	•	•	

TABLE VIII		OTHER Certifications & Options: (String in sequence comma delimited (XX, XX, XX,...))			Selection	L	S
Certifications & Warranty	None			00	•	•	
	Certificate of Conformance			F3			
	Calibration Test Report & Certificate of Conformance			F1			
	Extended Warranty Additional 1 year			01			
	Extended Warranty Additional 2 years			02			
	Extended Warranty Additional 3 years			03			
Extended Warranty Additional 4 years			04	•	•		

TABLE IX		Manufacturing Specials			Selection	L	S
Factory	Factory Identification			0000	•	•	

**MODEL RESTRICTIONS**

Restriction Letter	Available Only with		Not Available with	
	Table	Selection(s)	Table	Selection(s)
a	la	82A, 82B, 82C, 82D, 89A, 89B		
c	la	82A, 82B		
d	la	82A, 82B, 82C, 82D		
e	la	83A, 83B, 83C, 83D, 83E		
f	la	82C, 82D		
h	la	83A		
j			la	89A, 89B
k	la	82A, 82B, 82C, 82D, 83A, 83B, 83C, 83D, 83E		
m	la	83B, 83C		
n	la	83D, 83E		
b	Select only one option from this group			

HART® is a registered trademark of HART Communication Foundation.  
FOUNDATION™ Fieldbus is a trademark of Fieldbus Foundation.  
Viton® is a registered trademark of DuPont Performance Elastomers.  
Teflon® is a registered trademark of DuPont.  
FM Approvals<sup>SM</sup> is a service mark of FM Global

**FIELD INSTALLABLE REPLACEMENT PARTS**

Description	Kit Number
NCR Level HART Electronics module for Liquids	50155577-501
NCR Level HART Electronics module for Solids	50155577-502
NCR Level Display module	50155578-501

## Sales and Service

For application assistance, current specifications, ordering, pricing, and name of the nearest Authorized Distributor, contact one of the offices below.

### ASIA PACIFIC

Honeywell Process Solutions,  
Phone: + 800 12026455 or  
+44 (0) 1202645583  
(TAC) [hfs-tac-support@honeywell.com](mailto:hfs-tac-support@honeywell.com)

#### Australia

Honeywell Limited  
Phone: +(61) 7-3846 1255  
FAX: +(61) 7-3840 6481  
Toll Free 1300-36-39-36  
Toll Free Fax:  
1300-36-04-70

#### China – PRC - Shanghai

Honeywell China Inc.  
Phone: (86-21) 5257-4568  
Fax: (86-21) 6237-2826

#### Singapore

Honeywell Pte Ltd.  
Phone: +(65) 6580 3278  
Fax: +(65) 6445-3033

#### South Korea

Honeywell Korea Co Ltd  
Phone: +(822) 799 6114  
Fax: +(822) 792 9015

### EMEA

Honeywell Process Solutions,  
Phone: + 800 12026455 or  
+44 (0) 1202645583

Email: (Sales)  
[FP-Sales-Apps@Honeywell.com](mailto:FP-Sales-Apps@Honeywell.com)  
or  
(TAC)  
[hfs-tac-support@honeywell.com](mailto:hfs-tac-support@honeywell.com)

#### Web

Knowledge Base search  
engine <http://bit.ly/2N5Vldj>

### AMERICAS

Honeywell Process Solutions,  
Phone: (TAC) (800) 423-9883  
or (215) 641-3610  
(Sales) 1-800-343-0228

Email: (Sales)  
[FP-Sales-Apps@Honeywell.com](mailto:FP-Sales-Apps@Honeywell.com)  
or  
(TAC)  
[hfs-tac-support@honeywell.com](mailto:hfs-tac-support@honeywell.com)

#### Web

Knowledge Base search  
engine <http://bit.ly/2N5Vldj>

*Specifications are subject to change without notice.*

### For more information

To learn more about SmartLine Transmitters,  
visit [www.honeywellprocess.com](http://www.honeywellprocess.com)  
Or contact your Honeywell Account Manager

### Process Solutions

Honeywell  
1250 W Sam Houston Pkwy S  
Houston, USA, TX 77042

Honeywell Control Systems Ltd  
Honeywell House, Skimped Hill Lane  
Bracknell, England, RG12 1EB

Shanghai City Centre, 100 Jungi Road  
Shanghai, China 20061

[www.honeywellprocess.com](http://www.honeywellprocess.com)

# Honeywell

34-SL-03-06  
October 2020  
©2020 Honeywell International Inc.